

DC101

Magnetkontakt Aufbau, weiß

DC101-Series

The DC101-Series surface mount magnetic contacts are designed for use in installations where a small, sealed unit is required. The reed switch is totally encapsulated in an exclusive polyurethane potting compound preventing moisture from entering the switch and causing false alarms.

Easy installation

The 16 mm standard gap distance allows for fast, easy installation and prevents false alarms from loose fitting doors. Recessed mounting holes make for clean-looking installations.

High Quality components and materials

Reed legs are plated with rhodium or ruthenium, and hermetically sealed in dry nitrogen. This offers superior protection against sticking and provides a moisture free environment therefore preventing corrosion.



Einzelheiten

- Aufbaumagnetkontakt
- VdS Anerkennung: G 191501- gültig bis Ende Juni 2021

DC101

Magnetkontakt Aufbau, weiß

Technische Spezifikationen

Allgemein

Anwendungsart	Oberflächenmontage
Kontaktart	NC
Konnektivität	4 wires, 2 m

Kabelgebunden / drahtlos

Kabelgebunden / drahtlos	Verdrahtet
Schaltabstand	15 mm (max.)

Physikalisch

Abmessungen	51 x 9 x 9 mm
Farbe	Weiß

Umweltbedingungen

Material der Montagefläche	Ferrometall, Nicht-Ferrometall
----------------------------	--------------------------------

Regulativ

EN50131 Klasse	Klasse 2
----------------	----------

