

## 1 ROUREG™ OPEM

- Arbeidsstroom
- OPEM = mechanische ontgrendelpal

GC6

### TECHNISCHE GEGEVENS

Afmetingen h x b x d : 70,8 x 20,5 x 29,5 mm

Aansluitspanning	Stroomafname
8/12V AC/DC	700 mA
12V DC	200 mA
24V AC/DC	450 mA
24V DC	120 mA



## 1 ROUREG™ OPEM

<b>SE000228</b>	Elektrische deuropener 1 ROUREG OPEM 8-12V AC/DC - arbeidstroom	0,2 kg
<b>SE000231</b>	Elektrische deuropener 1 ROUREG OPEM 12V DC - arbeidstroom	0,2 kg
<b>SE000229</b>	Elektrische deuropener 1 ROUREG OPEM 24V AC/DC - arbeidstroom	0,2 kg
<b>SE000232</b>	Elektrische deuropener 1 ROUREG OPEM 24V DC - arbeidstroom	0,2 kg

## 1 ROUREG™ OPEM DIODE

<b>SE000237</b>	Elektrische deuropener 1 ROUREG OPEM diode 12V DC - arbeidstroom	0,2 kg
<b>SE000238</b>	Elektrische deuropener 1 ROUREG OPEM diode 24V DC - arbeidstroom	0,2 kg

BESCHIKBARE  
SLUITPLATEN :

Bladzijde 13



OPEM



GEINTEGREERDE  
BLUSDIODE

